

PRODUCT-DETAILS

C3SS2-10B-20**C3SS2-10B-20 Selector Switch****genel Bilgi**

Geniřletilmiř Ürün Türü	C3SS2-10B-20
Ürün Kimlięi	1SFA619211R1026
EAN	7320500555446
Katalog Açıklaması	C3SS2-10B-20 Selector Switch
Uzun Açıklama	<p>The C3SS2-10B-20 Selector Switch is: Compact - Selector Switch - 3-position - Momentary - Short handle - Black - Non-illuminated - Black Plastic - 2NO - 2 NO - 0 NC - 300 V</p> <p>This Selector Switch is part of ABB's compact range, the most efficient all-in-one solution available, reducing installation time and cost.</p> <p>The compact range has a high level of dust and water resistance.</p>

Ordering

Minimum Sipariř Miktarı	10 piece
Gümrük Tarifesi numarası	8536501999

Popular Downloads

Veri Sayfası, Teknik Bilgi	1SFC151007C02__
Talimatlar ve Kılavuzlar	1SFC151011M0201

Dimensions

Ürün Net Genişliği	0.03 m
Ürün Net Yüksekliği	0.03 m
Ürün Net Derinlik / Uzunluk	0.072 m
Ürün Net Ağırlığı	0.024 kg

Technical

Ortam Hava Sıcaklığı	Operation -25 ... +70 °C Storage -40 ... +85 °C
Color	Black
Actuator Type	Short handle
Bezel Material	Black Plastic
Illumination	Non-illuminated
Function	Momentary
Sub-Function	3-position
Spring Return From	A and C to B
Number of Auxiliary Contacts NC	0
Number of Auxiliary Contacts NO	2
Muhafaza Türü NEMA	Type1 Type12 Type13 Type3R Type4 Type4X
Rated Insulation Voltage (U _i)	300 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Nominal Frekans (f)	50 / 60 Hz
Nominal Çalışma Gerilimi	Maximum 300 V
Rated Operational Current DC-13 (I _θ)	(24 V) 0.3 A (125 V) 0.2 A
Rated Operational Current AC-15 (I _θ)	(240 V) 1 A
Power Loss	Maximum 5 W
Mechanical Durability	0.5 million
Connecting Capacity	Flexible with Ferrule 1 x 0.5...1.5 mm ² Flexible with Ferrule 2 x 0.5...1.5 mm ² Flexible with Insulated Ferrule 1 x 0.5...1.5 mm ² Flexible with Insulated Ferrule 2 x 0.5...1.5 mm ² Flexible 1 x 0.5 ...1.5 mm ² Flexible 2 x 0.5 ...1.5 mm ² Solid 1 x 0.5...1.5 mm ² Solid 2 x 0.5...1.5 mm ²
Terminal Türü	Screw Terminals
Sıkma Torqu	0.8 N·m
Wire Stripping Length	6 mm

Technical UL/CSA

Connecting Capacity UL/CSA	1x 22...14 AWG 2x 22...14 AWG
----------------------------	----------------------------------

Environmental

Koruma Derecesi	Front IP66 Front IP67 Front IP69K Terminals IP20
-----------------	---

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2022-006479
RoHS Bilgileri	2CMT2022-006498
RoHS Durumu	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006523
AEEE B2C / B2B	Business To Business
AEEE Kategorisi	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CB Certificate	CQC_CN_CN50749
CQC Certificate	CQC2003010305054693
cURus Certificate	UL_E496500-20171020
Declaration of Conformity - CCC	2020980305001187
Uygunluk Beyanı - CE	2CMT2015-005451
Declaration of Conformity - UKCA	2CMT2020-006121
DNV GL Certificate	9AKK107046A3749
EAC Certificate	RU C-CN.ME77.B.00587/20

Container Information

Paket Seviye 1 Birimler	bag 10 piece
Paket Düzey 1 Genişlik	0.235 m
Paket Seviye 1 Derinlik / Uzunluk	0.125 m
Paket Seviye 1 Yükseklik	0.035 m
Paket Seviye 1 Brüt Ağırlık	0.24 kg
Paket Düzey 1 EAN	7320500246993

Classifications

Nesne Sınıflandırma Kodu	S
ETIM 6	EC001029 - Selector switch, complete
ETIM 7	EC001029 - Selector switch, complete
ETIM 8	EC001029 - Selector switch, complete
eSınıf	V11.0 : 27371243
UNSPSC	39122217

IDEA Granüler Kategori
Kodu (IGCC)

5215 >> Selector Switch Complete Assemblies

E-Number (Finland)	2312909
E-Number (Norway)	4372795
E-Number (Sweden)	3711310

katagori

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range → CSS Compact Selector Switches

