



NB10W-TW01B

Touch screen HMI, 10.1 inch WVGA (800 x 480 pixel), TFT color, Ethernet + USB Host

Screen diagonal	10.1 in
Number of pixels, horizontal	800
Number of pixels, vertical	480
Type of display	TFT
Frame colour	Black
Number of Ethernet ports	1
Number of USB ports	2
Number of RS-232 ports	2
Number of RS-422 ports	1
Number of RS-485 ports	1
Number of colours of the display	65536
Number of grey-scales/blue-scales of display	64
Degree of protection (IP), front side	IP65
Width of the front	268.8 mm
Height of the front	210.8 mm
Width of panel cutout	258 mm
Height of panel cutout	200 mm
Built-in depth	54 mm
Product Weight (unpacked)	1950 g



CP1W-CN221



NB10W-KBA04

Accessory HMI, protective sheets for NB10W (5 sheets)



XW2Z-200T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 2 m



XW2Z-500T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 5 m

CAD Kütüphanesi



How to Import PLC Variables from Sysmac Studio

Uygulama Kılavuzu

EN PDF 534 KB



Maxell CR-series button cells

Pil Emniyeti Veri Sayfası

EN PDF 132 KB



NB Faceplate 3.1 - Multilanguage

Yazılım

EN ZIP 75,3 MB



NB Series HMI Veri Sayfası

TR PDF 1,38 MB



NB Series Programmable Terminal Broşür

EN PDF 3,26 MB



NB-Designer Setup v1.5.3.1

Yazılım

EN ZIP 374 MB



NB-Series Başlangıç Rehberi

EN PDF 9,83 MB



NB-Series Kurulum Kılavuzu

EN PDF 9,02 MB



NB-Series Host Connection Kurulum Kılavuzu

EN PDF 21,3 MB



NB-series Programmable Terminals (Europe)

Üretimden Kaldırılma Bildirimi

EN PDF 127 KB

WEB SİTESİ KULLANIM KOŞULLARI

Bu PDF belgesi, 24 May, 2024 tarihinde OMRON Endüstriyel Otomasyon Avrupa web sitesinden oluşturulmuştur. [yasal duyurular](#) için buraya tıklayın.